

## PT-15-12/PT-15-24

- 1) Isolation Class II
- 2) Withstand Voltage I/P-O/P: 3kVAC
- 3) Protection: Short circuit, Overload, Over voltage
- 4) Cooling by free air convection
- 5) Can be installed on DIN rail TS-35/7.5 or 15
- 6) LED indicator for power on
- 7) 100% full load burn-in test
- 8) 3 years warranty



Safety: EN60950  
 EMC Emission: EN55022 , EN61000-3-2  
 EMC Immunity: EN55024, EN61000-3-3



Model		PT-15-12	PT-15-24
Output	DC Voltage	12V	24V
	Rated Current	1.25A	0.63A
	Current Range	0~1.25A	0~0.63A
	Rated Power	15W	15W
	Ripple&Noise	120 mVp-p	150 mVp-p
	Voltage Adj.Range	<b>10.8-13.6V</b>	<b>21.6-29.0V</b>
	Hold Up Time	70ms/230VAC	
	Set up,Rise time	500ms, 20ms / 230VAC	
Input	Voltage Range	170-265 VAC 47~63Hz	
	Efficiency	<b>81%</b>	<b>83%</b>
	Ac Current	0.17A/230VAC	
	Inrush Current	Cold Start <20A at 230VAC	
Protection	Over Current	110~160% rated output power	
	Protection Type	Constant current limiting, recovers automatically after fault condition is removed	
	Over Voltage	Hiccup mode, recovers automatically after fault condition is removed	
Environment	Working Temp & Humidity	-20-60°C 20-90% RH	
	Storage Temp & Humidity	-40-80°C 10-90%RH	
Safety&EMC	Safety Standards	Design Refer to: EN60950	
	Withstand Voltage	I/P-O/P:3KVAC	
	Isolation Resistance	I/P-O/P:>100M Ohms / 500VDC	
	EMC Emission	Compliance to EN55022 , EN61000-3-2 ,	
	EMC Immunity	Compliance to EN55024, EN61000-3-3,	
Others	Dimension	<b>25*93*56mm (W*H*D)</b>	
	Packing	<b>0.097kg/pcs 100pcs/10.14kg/ctn</b>	